



Redding Reloading Equipment Cortland, NY 13045

www.redding-reloading.com techline@redding-reloading.com 607-753-3331

Stuck Case Removal Kit Instructions

Cases can become stuck when too little or poor quality case lubricant is used.

This case removal kit provides an easy solution to your problem.

Contains:

- No. 7 Drill
- 1/4 – 20 Tap
- Cap
- Allen Wrench
- 1/4 – 20 Cap Screw



The following procedure is to be followed when using the Stuck Case Removal Kit.

1. Remove die with the stuck case from your reloading press.
2. Remove decapping rod or back it out as far as possible.
3. Using the No. 7 drill provided, drill through the primer pocket and flash hole.
4. Using the 1/4 – 20 tap provided, tap the end of the stuck case. In the absence of a “tee” handle, simply secure the tap in your vise and turn the stuck case and die about the tap by hand.
5. Place the cap over the stuck case and insert the 1/4 – 20 cap screw as far as possible with fingers.
6. Insert allen wrench and continue turning cap screw until case is pulled from the die.
7. Use a little more of the proper lubricant next time, especially on the lower half of the case near the head.

If you have any questions regarding the above procedures, do not hesitate to contact our tech support members.

Email: techline@redding-reloading.com

Phone: (607) 753- 3331

Lifetime Warranty Disclaimer:

All Redding Reloading Equipment has been carefully inspected prior to shipment and is fully warranted to be free from defects in materials and workmanship for life.

Any product or parts which prove to be defective will be replaced or repaired without charge if returned prepaid to the factory.

Note: We reserve the right to decline responsibility where misuse or careless handling is evident or where repairs or modifications have been made or attempted by others.